

Industry-Leading Protection for Your Home

MAXIMUM STRENGTH

Precision-engineered system with unparalleled strength to protect from forced entry threats and the strongest hurricane winds.

SUPERIOR AESTHETICS

Smallest shutter box in the industry across all motorized and manual models to minimize visible footprint.

ENHANCED OPERATION

Patented nesting design and bushing-guide system provide reliable, smooth, and quiet operation.

HIGH DURABILITY

Hinge and slat design reduces risk of water and sand infiltration, and provides greater resistance to dents and dings.

INSTALLATION FLEXIBILITY

Wide range of manual and motorized configurations to efficiently cover more openings on your home. Locking slat options to support windows, doors, patio step-downs and other application needs.

Features Summary

DIMENSIONS

- 24 - 236 in. (Width) (2 ft. - 19 ft. 8 in.)
- 24 - 288 in. (Height) (2 ft. - 24 in.)

SLATS

- Solid single wall extruded 6063-T6 aluminum 0.055 in. thick, in 12 heights (Nesting)
- Retained in curtain with 3 in. stainless steel screws with nylon shoulder bushings
- Mid-curtain slat configurations for manual operation

GUIDE RAILS

- 6063-T6 Aluminum lined with polypropylene runners and felts
- 3-1/4 in. W Retained rail with snap cover for motorized shutters
- 3-3/4 in. W Retained rail with spring stop and snap cover for manual shutters

BOTTOM BAR (BASE SLAT)

- Standard and low-profile (Motorized)
- Slide lock, thumbturn, and stop-bar only (Manual)

BOX HOUSING

- 3105-H12 alloy 0.034 in. thick 6063 - T6 aluminum in 6, 6.5, 7, and 8 in. sizes

Options Summary

BOX HOUSING SHAPE

- 90° angle (square), 45° angle, or round styles

OPERATOR

- Motor
- Motor with override
- Remote (Hz) motor
- Remote (Hz) motor with override
- Battery (EZ) motor
- Manual (Spring-Assist)
- Manual (Gear)

LOCKS

- Base Slat Slide Lock
- Base Slat Thumbturn (Key or No Key)
- Mid-curtain cylinder key

COLORS

- White, Gray, Bronze, Beige, and Ivory. Powder and wet paint.
 - SH - Series Powder coat Per AAMA 2603-13, DFT 60 - 110 µm
 - H/S Polyester 221T2602 DuraCoat wet paint, DFT 24 - 28 µm
- Clear (Silver) and Black Anodize Type II, Class 2, 10µm

MOUNT


- Wall, Trap, Build-out mounting to structure

WARRANTY*



* Applies to Residential Applications only and homeowner who follows Use and Care Guidelines

Hurricane Certifications



Florida Building Code (FBC) (HVHZ & non-HVHZ) (No. FL39156-R4)

Miami-Dade (NOA) (No. 23-1010.06, 23-1010.07)

Texas Department of Insurance (TDI) (No. SHU-243)

Note: Testing in accordance with TAS 201/202/203 and ASTM E330/E1886/E1996 Missile Level D